




Autonomous Optimization

The Unico SRP Variable Speed Drive provides autonomous optimization for rod pumped wells by utilizing patented algorithms and digital twins to continuously maximize production while ensuring pumping unit integrity.

Unico SRP drive's embedded software integrates motor control, well optimization, pump fill control, and rod load control into a single, compact solution enhancing usability, energy efficiency and reliability of both new and existing pumping systems.




Simple Guided Setup


Everything you need at your fingertips

- Well performance
- Setup
- Operation

View Predicted to Measured Dynacards

Easy troubleshooting and validation of setup





Performance Notifications

Pump Expert™ diagnostics identifies possible issues





Why Unico SRP Drives are the Leaders in Optimization Automation

Patented algorithms in the drive maximize production while protecting the pumping system.

Production Optimization

- Pump Fill Control
- FOP/PIP Calculation
- Speed Profiler Mode
- Automatic Unmanned Valve Check
- Auto Pump Fill Setpoint Adjustment
- Stuck Pump Mode
- Pump Clean [™] Mode
- Diluent control
- DH Friction Calculation
- Gas Interference Controller

Energy Efficiency

- Balance assistant
- Improved Power Factor
- Optimum Speed Control

- Solar Power Optimizer
- Flat Power
- Regen/Motor Power Limiter

Equipment Protection

- Soft Landing
- Sensorless Control
- Rod Load Control
- Pump Diagnostics

- Gearbox Torque Limiter
- Bridle Separation Control
- Rotaflex® Park Assist
- Belt Slip Detection

Advanced Features

- UEDIT®- built in soft PLC capability
- System Modeling Digital Twin
- PMM Control
- Well Analytics
- Pump/Rod Velocities/Position

- Pump Expert[™]
- Fault / Event History
- Technical Support/Training
- Remote Connectivity
- Mobile Device Connectivity



Unico SRP Variable Speed Drive

Simplified Sophistication

Built on decades of automation experience and success, Unico SRP Variable Speed Drives give you the ability to match its functions and features with your unique requirements.

Intelligent features and multi-level access to controller data and diagnostics further enhance operations at the well site and remote.

Autonomous control settings can be setup for each well site, providing hands-free optimization.

General Specifications

- Input Voltage: 380-460vac, 575vac ±10%
- Power Range: 10-300 HP (7.5kw 225kw)
- Enclosure: NEMA 4 (IP55)
- Operating temp: -40° to 104°F (-40° to +40°C)

 up to 122°F (+50°C) with de-rating
- Listing: UL ,CE available



UNITED STATES

CORPORATE HEADQUARTERS 3725 Nicholson Rd. P. O. Box 0505 Franksville, WI 53126-0505 (262) 886-5678

COLOMBIA

Centro Empresarial Metropolitano KM. 3.4, Calle 80-Via Siberia-Cota Modulo 1, Bodega 6

+(57-1)-7469550/7469569 +57 -3173650663



UNITED KINGDOM

Unico (UK) Ltd.
Garamonde Drive Wymbush
Milton Keynes MK8 8LF
+44.1908.260000



(Manufacturing, Engineering, Sales And Service) Unit 3, 553 Boundary Road Darra, Queensland 4076

+61.7.3713.7830 +61(0)439.700.548



Scan to Visit Our Website

GERMANY

Unico Deutschland GmbH Dortmunder Straße 7 D-57234 Wilnsdorf +49.2739.303.0

CANADA

1515 Matheson Blvd, East Unit # B5 Mississauga, Ontario L4W 2P5 Canada (905) 602-4677



All trade designations are supplied without reference to the rights of their respective owners.

Specifications subject to change without notice.

1100.21(014)

5/23